



24HxxKV0xx

Small countersunk head hexagonal body open stainless steel rivet nut (rivet nut)

Material: Stainless steel



Ød *Side width mm	l: length (mm) +0,5/-0	Grip range mm	Part no.	Ødk mm	k mm	Ød [+0/- 0,12] mm	Torque (Nm)	Tensile Newton	Shear Newton	Description
M4 *SW1 6,1	12,0	0,5-2,5	24H04KV025	6,5 [+0/-0]	≤0,9	6,0	12,0	8 240	2 950	Reduced head A2 hexagonal M04 rivet nut
M4 *SW1 6,1	12	1,5-3,0	24H04KV030	7 [+0/-0]	≤0,9	6	12,0	8 240	2 950	Small CSK head hexagonal Inox M04 rivet nut
M4 *SW1 6,1	13	2,5-4,0	24H04KV040	7 [+0/-0]	≤0,9	6	12,0	8 240	2 950	Small head hexagonal body Inox open M04 rivet nut
M5 *SW1 7,1	14,0	0,5-3,0	24H05KV030	7,5 [+0/-0]	≤0,9	7,0	11,0	11 760	2 840	Reduced head hexert A2 open M05 pop nut
M5 *SW1 7,1	13	2,5-4,5	24H05KV045	8 [+0/-0]	≤0,9	7,0	11,0	11 760	2 840	Small CSK head A2 hexagonal M05 rivet nut
M6 *SW1 9,1	16,0	0,5-3,0	24H06KV030	9,5 [+0/-0]	≤0,9	9,0	21,0	21 560	3 820	Reduced head hexagonal Inox M06 rivet nut
M6 *SW1 9,1	16	2,0-4,5	24H06KV045	10 [+0/-0]	≤0,9	9,0	21,0	21 560	3 820	Small head hexagonal body Inox open M06 rivet nut
M8 *SW1 11,1	17,0	0,5-3,0	24H08KV030	11,5 [+0,5/-0]	≤0,9	11,0	30,0	24 500	3 920	Small CSK head hexert A2 open M08 pop nut
M10 *SW1 13,1	20,5	1,0-4,0	24H10KV040	13,5 [+0,5/-0]	≤1,1	13,0	40,0	47 040	5 010	Reduced head A2 hexagonal M10 rivet nut

Technical specifications:

- can be set from one side, where the rear of the material and the inside of the object are inaccessible
- it is suitable for riveting of sheets and you get useable thread also
- not necessary to cut a thread or to weld a nut to the sheet (timesaving)
- material of sheet will not be deformed/ discolored
- suitable for thin sheet
- thanks to hexagonal body it is more secured against turning compared to cylindrical rivet nut
- better torque
- counter-boring is not necessary, despite of this the rivet nut head will stand out minimum from the surface (max. 0,5 mm)
- stainless