



24MxxKVO: Small countersunk head open stainless steel knurled rivet nut (micro head rivet nut)

Material: Stainless steel



Ød * Drill hole mm	l: length (mm) +0,5/-0	Grip range mm	Part no.	Ødk mm	k mm	Ød [+0/- 0,121 mm	Torque [Nm]	Tensile Newton	Shear Newton	Description
M4 Ø 6,0	10,0	0,5-2,5	24M04KV025	7,0 [+0/-0,5]	≤0,9	5,9	9,0	6 860	2 940	Small Countersunk Inox M04 rivet nut
M5 Ø 7,0	11,5	0,5-3,0	24M05KV030	8,0 [+0/-0,5]	≤0,9	6,9	10,5	11 760	4 030	Micro head A2 M05 rivet nut
M6 Ø 9,0	14,0	0,5-3,0	24M06KV030	10,0 [+0/-0,5]	≤0,9	8,9	21,0	18 620	5 230	Small countersunk head inox M06 rivet nut
M8 Ø 11,0	15,5	0,5-3,0	24M08KV030	12,0 [+0/-0,5]	≤0,9	10,9	31,0	25 480	5 400	Micro head A2 M08 pop nut
M10 Ø 13,0	19,5	0,8-3,5	24M10KV035	14,5 [+0/-0,5]	≤1,1	12,9	32,0	33 320	5 880	Small Countersunk Inox M10 rivet nut

Technical specifications:

- can be set from one side, where the rear of the material and the inside of the object are inaccessible
- it is suitable for riveting of sheets and you get useable thread also
- not necessary to cut a thread or to weld a nut to the sheet (timesaving)
- material of sheet will not be deformed/ discolored
- suitable for thin sheet
- counter-boring is not necessary, despite of this the rivet nut head will stand out minimum from the surface (max. 0,5 mm)
- stainless