



## 26MxxKV0xx Small countersunk head open steel rivet nut (micro head rivet nut, pop nut)

Material: Steel, RoHS surface treatment



Ød * Drill hole mm	l: length (mm) +0,5/-0	Grip range mm	Part no.	Ødk mm	k mm	Ød [+0/- 0,12] mm	Torque (Nm)	Tensile Newton	Shear Newton	Description
M3 Ø 4,8	9,0	0,5-1,5	26M03KV015	5,4 [+0/-0,31]	≤0,6	4,7	1,5	2 690	980	Small Countersunk open M03 rivet nut
M4 Ø 6,4	10,4	0,5-2,0	26M04KV020	6,9 [+0/-0,31]	≤0,6	6,3	5,0	6 800	1 080	Micro head open M04 rivet nut
M5 Ø 7,2	11,8	0,5-3,0	26M05KV030	7,7 [+0/-0,31]	≤0,6	7,1	8,0	8 000	1 470	Small countersunk head open M05 rivet nut
M6 Ø 9,6	14,6	0,7-3,3	26M06KV033	10,5 [+0/-0,31]	≤0,8	9,5	12,5	11 400	1 960	Micro head open M06 pop nut
M8 Ø 10,6	16,0	0,9-3,7	26M08KV037	11,5 [+0/-0,31]	≤0,8	10,6	16,5	15 700	2 940	Small Countersunk open M08 rivet nut
M10 Ø 14,2	18,5	1,0-3,6	26M10KV036	15,3 [+0/-0,31]	≤0,8	14,2	34,0	18 700	3 920	Micro head open M10 rivet nut

### Technical specifications:

- can be set from one side, where the rear of the material and the inside of the object are inaccessible
- it is suitable for riveting of sheets and you get useable thread also
- not necessary to cut a thread or to weld a nut to the sheet ( timesaving)
- material of sheet will not be deformed/ discolored
- suitable for thin sheet
- counter-boring is not necessary, despite of this the rivet nut head will stand out minimum from the surface (max. 0,5 mm)