



2C7MxxV0xx Small countersunk head open steel knurled rivet nut (micro head rivet nut, pop nut)

Material: Steel, RoHS surface treatment



Ød Drill hole mm	l: length (mm) +0,5/-0,5	Grip range mm	Part no.	Ødk mm	k mm	Ød [+0/- 0,12] mm	Torque (Nm)	Tensile Newton	Shear Newton	Description
M4 Ø 7,0	10,5	0,5-3,0	2C7M04V030	8,0	≤0,5	7,0	-	-	-	Small Countersunk open M04 rivet nut
M5 Ø 7,0	11,5	0,5-3,0	2C7M05V030	8,0	≤0,5	7,0	-	-	-	Micro head open M05 rivet nut
M6 Ø 8,0	13,0	0,5-3,0	2C7M06V030	9,0	≤0,5	8,0	-	-	-	Small countersunk head open M06 rivet nut
M8 Ø 10,0	15,5	0,5-3,0	2C7M08V030	11,0	≤0,5	9,9	-	-	-	Micro head open M08 pop nut

Technical specifications:

- can be set from one side, where the rear of the material and the inside of the object are inaccessible
- it is suitable for riveting of sheets and you get useable thread also
- not necessary to cut a thread or to weld a nut to the sheet (timesaving)
- material of sheet will not be deformed/ discolored
- suitable for thin sheet
- counter-boring is not necessary, despite of this the rivet nut head will stand out minimum from the surface (max. 0,5 mm)